



- > Black & White MFP
- > Small Workgroup
- > Copy, Print, Scan, Fax*





Small footprint, big output.

If the Toshiba e-STUDIO2505H/2505F were simply a letter-sized MFP, you'd be impressed. But we didn't stop there. We kept going until 11" x 17" output could be printed using the bypass. What more could you ask for from such a small footprint and price?

Small businesses, big benefits.

Toshiba technology and functionality are now available in a power-packed, lettersized printer with large, ledger-sized support. The e-STUDIO2505H/2505F MFP delivers impressive black and white output at 25 pages per minute. You can copy, print, and scan—including precise color scanning—and even fax, with the e-STUDIO2505F. Network connectivity and USB 2.0 come standard, with 802.11 B/G/N wireless connectivity available as an option. In short, small offices and workgroups can take advantage of everything Toshiba has to offer for today's budgetconscious, results-oriented businesses.

Features galore.

Don't be fooled by the small footprint. In addition to offering ledger printing via the bypass, the e-STUDIO2505H/2505F has a 300-sheet capacity when you combine the bypass with the 250-sheet cassette. Also using the bypass, you can print professional looking envelopes to your exact specifications. There is also an ID card copying feature, and automatic duplexing comes standard. Warm-up time is an impressive 20 seconds, with the first copy out in just 7.1 seconds. Whatever you want from an affordable, letter-sized MFP, the e-STUDIO2505H/2505F has it, and more. Now smaller businesses can think big with the power, functionality, networking capabilities, and ledger-size output to back it up.



C-STUDIO 2505H/2505F



> Digital MFP

- > Ledger Support Via Bypass
- > Network Connectivity
- > Automatic Duplexing
- > Color Scanning
- > Standard Fax*
- > Optional Wireless Connectivity





Doing more for our planet.


From our zero-waste-tolandfill toner recycling to greener manufacturing, Toshiba is a recognized environmental leader. At Toshiba we're investing in programs that help both our business and yours to better reduce, reuse and recycle.



Handle multiple functions with the easy-to-use control panel. Scan to USB drives and other portable devices. Just plug in, and go. Network connectivity and USB 2.0 come standard.

Why settle for less?

Speed, versatility, reliability and affordability. The benefits are as impressive as the features. Like department code support—up to 100 codes, an electronic counter, auto job start, 2400 x 600 dpi (with smoothing), and scan to USB. You'll find just as much, if not more, from the e-STUDIO2505H/2505F. All packed into a footprint that small businesses can appreciate. Letter or ledger, scan or copy, network or USB, the e-STUDIO2505H/2505F makes more available, for less. It's the MFP you've been waiting for.







C-STUDIO[®]2505H/2505F



General Specifications

| TypeDesktopOriginal scanning methodContact Image Sensor (CIS)Resolution2400 x 600 dpi (with smoothing)Gradation256 stepsOriginal Platen TypeFixed hard platen, ADFAvailable Original SizeST-R, LDAvailable Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets) Available Paper WeightPaper ExitDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitSprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H)WeightApprox. 47.3 lbs. | Copying/Printing process | Indirect electrostatic photographic method |
|---|--------------------------|---|
| Resolution2400 x 600 dpi (with smoothing)Gradation256 stepsOriginal Platen TypeFixed hard platen, ADFAvailable Original SizeST-R, LDAvailable Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Туре | Desktop |
| Gradation256 stepsOriginal Platen TypeFixed hard platen, ADFAvailable Original SizeST-R, LDAvailable Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Original scanning method | Contact Image Sensor (CIS) |
| Original Platen TypeFixed hard platen, ADFAvailable Original SizeST-R, LDAvailable Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Resolution | 2400 x 600 dpi (with smoothing) |
| Available Original SizeST-R, LDAvailable Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Gradation | 256 steps |
| Available Paper SizeDrawer: LT only Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Original Platen Type | Fixed hard platen, ADF |
| Stack Feed Bypass: ST-R, LD EnvelopePaper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lbStack Feed Bypass: 17-90 lbAuto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Available Original Size | ST-R, LD |
| Paper SupplyDrawer (250 sheets x 1) and Stack Feed Bypass (50 sheets)Available Paper WeightDrawer: 17-20 lbAvailable Paper WeightStack Feed Bypass: 17-90 lbAuto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Available Paper Size | Drawer: LT only |
| Available Paper WeightDrawer: 17-20 lb Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | | Stack Feed Bypass: ST-R, LD Envelope |
| Stack Feed Bypass: 17-90 lb Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Paper Supply | Drawer (250 sheets x 1) and Stack Feed Bypass (50 sheets) |
| Auto Duplexing Unit: 17-20 lbPaper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Available Paper Weight | Drawer: 17-20 lb |
| Paper ExitFace down/Inner TrayWarm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | | Stack Feed Bypass: 17-90 lb |
| Warm-up TimeApprox. 20 secondsCounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | | Auto Duplexing Unit: 17-20 lb |
| CounterElectronic counter (indication by LCD display)Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Paper Exit | Face down/Inner Tray |
| Memory512 MBPower Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Warm-up Time | Approx. 20 seconds |
| Power Supply110 VPower ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Counter | Electronic counter (indication by LCD display) |
| Power ConsumptionMax. 1.5kWDimensions15.3 x 21.25 x 20 (W x D x H) | Memory | 512 MB |
| Dimensions 15.3 x 21.25 x 20 (W x D x H) | Power Supply | 110 V |
| (,, | Power Consumption | Max. 1.5kW |
| Weight Approx. 47.3 lbs. | Dimensions | 15.3 x 21.25 x 20 (W x D x H) |
| | Weight | Approx. 47.3 lbs. |
| Special Features Energy Saver, Auto Sleep Mode, Department code | Special Features | Energy Saver, Auto Sleep Mode, Department code |
| Max Duty Cycle 50K Copies | Max Duty Cycle | 50K Copies |

> Black and White MFP

> Small Workgroup > Copy, Print, Scan, Fax

> Secure MFP

> 25 PPM

Paper Handling Options

| Standard Automatic Document Feeder (ADF) | |
|--|-----------|
| Stack Capacity | 50 sheets |
| Original Setting | Face up |
| Original Paper Size | ST-R, LD |
| Original Paper Weight | 17-20 lb |

*Walk-up FAX Specifications (e-STUDIO2505F only)

| Compatibility | Super G3, G3 |
|-------------------------|---|
| Image Format on PSTN | JBIG, MMR, MR, MH |
| Document Size | ST-R-LD |
| Modem Speed | 33.6kbps to 2.4kbps (automatic fallback) |
| Transmission Speed | Approx. 3 seconds |
| Communication Protocols | ITU-T T.30 |
| Memory Transmission | Max 256 Jobs, 220 Destinations/Job, 1000 Pages/File |

Options

....

Wireless LAN Module (ETA Nov. 2013) GN1080 Damp Heater (for Drum) MF2505U Harness for Coin Controller GQ1131

Copy Specifications

| Copying Speed | 25 PPM |
|-----------------------|---|
| Original Scan Speed | 20 SPM (by using ADF) |
| Scan Resolution | 600 x 600 dpi (for copying) |
| First Copy Time | 7.1 seconds |
| Original/Copy Size | ST-R to LD |
| Original Mode | Photo, Text/Photo, Text, Background Erase |
| Image Density Control | Automatic/Manual (11 steps) |
| Reproduction Ratio | Zoom: 25 % to 400 % in 1 % increments |
| Multiple Copying | Up to 999 copies (Ten key input) |
| Special Features | Interrupt, APS/AMS, Auto job start, Automatic sort mode, |
| Special Features | Interrupt, APS/AMS, Auto job start, Automatic sort mode, ID card copy |

Print Specifications (Standard)

| Printing Speed | 25 PPM |
|---------------------|--|
| Printing Resolution | 2400 x 600 dpi (with smoothing) |
| Interface | Standard: 10/100 Base-T, USB 2.0, |
| | Optional: 802.11 b/g/n |
| PDL | PCL 6 emulation |
| Support OS | Windows 7/8/XP/Vista/Server 2003/2008/2008R2 |

Scan Specifications (Standard)

| Connection Type | Standard: 10/100 Base-T, |
|---------------------|--|
| | Optional: 802.11 b/g/n |
| Scanning Resolution | 100/150/200/300/400/600 dpi |
| Scanning Speed | 20 SPM (BW), 5 SPM (Color) |
| Scan Agent | Scan to File, SMB, FTP, Scan to Email, Scan to USB |



| Corporate Office | 9740 Irvine Blvd., Irvine, CA 92618 |
|------------------|--|
| | Tel: 949-462-6000 |
| East Coast | 959 Route 46 East, 5th Floor, Parsippany, NJ 07054 |
| | Tel: 973-316-2700 |
| Midwest | 8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 |
| | Tel: 773-380-6000 |
| South | 2037 Bakers Mill Rd., Dacula, GA 30019 |
| | Tel: 678-546-9385 |
| West Coast | 9740 Irvine Blvd., Irvine, CA 92618 |
| | Tel: 949-462-6000 |
| Web Site | www.business.toshiba.com |
| | |

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

© 2013 Toshiba America Business Solutions, Inc. Electronic Imaging Division Inv. Code 22226 2505H/2505F Brochure 5K PG 7/13